

Thank you for purchasing Yamaha products.  
Please be sure to read this owner's manual carefully before installation.

このたびは、ヤマハ製品をお買い求めいただき、誠にありがとうございます。  
取り付けの前に、この取扱説明書をよくお読みください。よろしくお願いいたします。

## PRECAUTION / ご注意

## ⚠ WARNING

- Never attach a speaker weighing more than 4 kg. The stand may break resulting in injury.
- Make sure you attach the stand to a location of sturdy material. If the material is weak, the stand may drop resulting in injury.

## ⚠ CAUTION

- Do not use the speaker clamp for anything other than its intended purpose. The stand may break resulting in injury.
- Make sure all screws are securely tightened. Also, when the stand is used over a long period of time, periodically check the screws for tightness. Using the stand with loose screws it may drop resulting in injury.
- Yamaha shall not be responsible for any accidents due to improper selection of installation position or faulty installation. Therefore, make sure to select a place strong enough to hold a speaker and check to ensure for safety after installation.
- Make sure to tighten each screw securely and check that the speaker system is held stationary.
- Do not apply force, impact or vibration to the attachment or speaker.

## ⚠ 警告

- 4kg以上のスピーカーで使用しないでください。破損してけがをすることがあります。
- 台座は頑丈な場所に確実に取り付けてください。取り付け部が弱いと落下してけがをすることがあります。


## ⚠ 注意

- スピーカークランプ以外の目的で使用しないでください。破損やけがをすることがあります。
- ネジは確実に締めてください。また長時間使用する場合は、緩んでないことを確認してください。  
緩んだまま使用するとスピーカーが落下してけがをすることがあります。
- 取付箇所、取り付けの不備などによる一切の事故の責任は負いかねます。取付箇所は充分に強度のある場所を選び、取付後は必ず安全を確認してください。
- 各部のネジは確実に締め、スピーカーシステムが動かないことを確認してください。
- 機器に力を加えたり、衝撃や振動を与えないでください。

## INSTALLATION PROCEDURES / 取り付け手順

- Install the arm of BAS-10 to the underside or side of the speaker by tightening speaker fixing screws securely.
- Tighten the angle adjusting screw temporarily so that the speaker will not move.
- Install the base of BAS-10 at the desired sturdy position by tightening the base fixing screw securely.
- Insert the arm shaft into the hole in the base and tighten the arm shaft fixing screw.
  - As the arm shaft is hexagonal, tighten on its flat face.
  - For the purpose of safety, tighten with the arm shaft projecting more than a few centimeters out from the hole in the base.
- Direct the speaker so that it faces the listening point properly. Be sure to loosen the screw for angle adjustment.

- スピーカーにBAS-10のアーム部を取り付けます。  
スピーカー取り付けネジをスピーカーの底面または側面に締めつけて固定してください。
- 角度調節ネジをスピーカーが動かないように仮締めします。
- BAS-10の台座を設置場所に取り付けます。  
台座固定用ネジで頑丈な場所に確実に締めつけてください。
- 台座の穴にアームシャフトを差し込み、アームシャフト固定ネジを締めつけます。
  - アームシャフトは六角棒になっていますので、シャフトの平らな面を締めつけるようにしてください。
  - 安全のため、アームシャフトが台座の穴より数センチ以上突き出た状態で締めつけてください。
- スピーカーがリスニングポイントの方向に向くようにします。  
方向の調整は、必ず該当するネジをゆるめてから行ってください。




\* Weight (重量) : 750g (1lbs. 10oz)

ヤマハ株式会社

音響システム事業部 営業部 ☎ 053-460-2455  
〒430-8650 浜松市中沢町10-1

YAMAHA CORPORATION  
Pro Audio Division, #18/3  
P.O. Box 3, Hamamatsu, 430-8651, Japan  
Printed in Japan



\* The wire is not supplied with the unit.  
※補助ワイヤーは付属していません。